



SRW® Screens LCr-76, 78, 79 Series

Toyota Landcruiser 70 Series (1VD-FTV Engine)

4.5L V8 Intercooled Turbo Diesel

SRW® Screens - Intercooler & Radiator Screens Patent Pending

Toyota Landcruiser 70 Series Radiator Screen Installation Guide

What's in the pack: 2 x SRW Screens (1xPS & 1xDS) – LCr-70 Series Radiator Screens, 8 x cable ties, 1 x Installation Guide.

> Before you begin

Prior to commencing installation it is the installer's responsibility to verify that all components are correct, not damaged and free of defects.

IMPORTANT: Please note the Passenger Side (PS) and Drivers Side (DS) screens are slightly different in size. Ensure you install the correct screen on each side.

> STEP 1

Remove bottom O.E.M or aftermarket Radiator Guard, some Bull Bars also have a Bash Guard that needs to be removed.



> STEP 2

Bend Horizontal OEM plate & nut welded to passenger side of cross bar to Vertical (place large screw driver or chisel behind nut and tap with hammer)



> STEP 3

Position Screens behind grille either side of bonnet latch vertical support locating cable tie mounts in grille as per photo.

Secure top cable ties to grille loosely then **secure bottom cable ties to cross bar loosely.**

While holding each screen in correct positions tighten **TOP** cable ties evenly.

Position bottom of each screen ensuring even gap between screens and tighten **BOTTOM** cable ties.



> STEP 4

Re install bottom O.E.M or aftermarket Radiator Guard and Bash Guard if removed.



> Cleaning Guide

Our experience is that most bugs trapped by the SRW® Radiator screens break down over a short period of time (a couple of weeks).

If required the screens can be cleaned without being removed with a low pressure hose from behind the grille hosing towards the front of the vehicle.